

# W320UST

Ultra short throw projector



- **Bright WXGA projector - 4000 ANSI lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **Ultimate Control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Easy connectivity - 2x HDMI and built-in 16W speaker**



The W320UST is perfect for businesses, schools and colleges. It is bright (4,000 lumens) and a throw ratio of 0.27:1 means that it can project a 100" image from less than 0.5m away. And having the projector installed so close to the screen avoids any shadows being cast across the screen from the presenter(s).

# Specifications

EAN: 5055387628618, Colour: White



<b>Display/image</b>	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness	4.000 lumens
Contrast ratio	20.000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-15°
Horizontal scan rate	15.3 ~ 91.1Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	2.16m ~ 2.92m (85" ~ 115") diagonal

<b>Lamp info</b>	
Light source type	Lamp
Lamp watts	260
Lamp life hours (up to)	3000 (Bright), 5000 (Dynamic), 5000 (Eco), 6500 (Eco+), 12000 (Education)
Lamp life (education)	12.000 hours

<b>Optical</b>	
Throw ratio	0.27:1
Projection distance (m)	0.49m - 0.66m
Zoom type	Fixed
Focal length (mm)	3.72
Native offset	117%

<b>Connectivity</b>	
Connections	<b>Inputs</b> 2 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 1 x Audio RCA L&R <b>Outputs</b> 1 x VGA shared with VGA2, 1 x Audio 3.5mm, 1 x USB-A power 2A <b>Control</b> 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x mini USB mouse/service, 1 x 3D sync

<b>General</b>	
Noise level (typical)	28dB
Noise level (max)	30dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	16W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDcast Pro, QuickCast Bundle, QuickCast starter kit, WHD200

<b>Networking</b>	
LAN - control	Yes

<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	260W
Power consumption (max)	310W

<b>Weight and dimensions</b>	
Dimensions (W x D x H) mm	385 x 310 x 120
Gross weight	6.59 kg
Net weight	5.6 kg

