## WU335

High resolution, versatile and powerful



- Easy connectivity 2x HDMI, MHL, USB Power, • **RJ45**
- Clear, powerful audio 10W speaker •
- Lightweight and portable •

WU335 projector. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts easy connectivity with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even use the USB Power to connect and power HDMI dongles such as the Google Chromecast.

Beam bright, eye catching content with the high definition, WUXGA









## **Specifications**

EAN: 5055387660168, Colour: W	hite
Display/image	
Display technology Resolution	
Resolution Brightness	WUXGA (1920x1200)
0	3,600 lumens
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Uniformity	70%
Screen size	0.74m ~ 7.62m (29" ~ 300") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240 4000 (Brinkt) 10000 (Bringersin) 10000 (East) 15000 (East)
Lamp life hours (up to)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1.47:1 ~ 1.62:1
Projection distance (m)	1m - 9.5m
Zoom	1.1 Marcal
Zoom type	Manual
Focal length (mm)	15.59mm~17.14mm/0.614"~0.675"
Native offset	110%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	<b>Control</b> 1 x RS232, 1 x RJ45
General	
Noise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 4801/p, 5761/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Card style
Speaker count	1
Watts per speaker	10W
In the box	AC power cord, remote control, Battery, basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
	205W
Power consumption (min)	
Power consumption (min) Power consumption (max)	295W
Power consumption (max)	29500
Power consumption (max) Weight and dimensions	295W 316 x 244 x 108





Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 26082023060141