

X304M

Professional presentations on the move



- **Small, lightweight and portable**
- **Bright XGA projector – 3000 ANSI lumens**
- **Easy connectivity - HDMI, VGA and built-in speaker**
- **Full3D**

Ideally partnered with a notebook or a mobile device, the X304M delivers bright vivid presentations and videos in the office or on the road.

Weighting only 1.4kg, this travel-friendly projector incorporates a staggering 3000 ANSI lumens allowing you to project bright, crystal clear presentations during the day, leaving your audience speechless every time the projector is turned on.



Specifications

| | |
|--------------------------------|--|
| Display/image | |
| Display technology | DLP |
| Resolution | XGA (1024x768) |
| Brightness | 3,000 lumens |
| Contrast ratio | 10,000:1 |
| Native aspect ratio | 4:3 |
| Aspect ratio - compatible | 16:9, 16:10 |
| Keystone correction - vertical | +/-30° |
| Horizontal scan rate | 15 ~ 91.4KHz |
| Vertical scan rate | 43 ~ 87(120 for 3D)Hz |
| Uniformity | 85% |
| Screen size | 0.85m ~ 6.58m (33.58" ~ 259.25") (diagonal) |
| Lamp info | |
| Light source type | Lamp |
| Lamp watts | 220 |
| Lamp life (hours) | 4000 (Bright), 5000 (Eco) |
| Optical | |
| Throw ratio | 1.9:1 - 2.2:1 |
| Projection distance (m) | 1.2m - 10m |
| Zoom | 1.15 |
| Zoom type | Manual |
| Focal length (mm) | 21.3 ~ 24.5 |
| Native offset | 114% |
| Connectivity | |
| Connections | Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB/wireless), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm Control 1 x USB-B mouse/service |
| General | |
| Noise level (typical) | 33dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 2D compatibility | Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| 3D compatibility | Full 3D |
| 3D | Security bar, Kensington Lock, Password protected interface |
| Remote control | Data remote with laser and mouse function |
| Speaker count | 1 |
| Watts per speaker | 1W |
| In the box | Carry bag Lens cap AC power cord Remote control 2x AAA batteries Basic user manual |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 230W |
| Power consumption (max) | 280W |
| Weight and dimensions | |
| Net weight | 1.4kg |
| Dimensions (W x D x H) mm | 220 x 178 x 71 |

