

## ZH420

Eco-friendly ultra-compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -4300 lumens, 4K/HDR compatible & IP6X certified
- Small form factor for easy installation 1.3x zoom, 360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH420 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.<sup>1</sup>

An added benefit, the ZH420 features an external power supply offering more reliability, portability and energy efficiency.

## **Specifications**

EAN: 5055387666801, Colour: White

UPC: 796435 44 643 7, Colour: White

Display/image

Display technology DLP™

Resolution 1080p Full HD (1920x1080)

**Brightness** 4.300 lumens Contrast ratio 300,000:1 2,000,000:1 Contrast ratio - dynamic 16:9 Native aspect ratio 4:3 16:9 16:10 Aspect ratio - compatible

Keystone correction -

horizontal

+/-30°

Keystone correction - vertical +/-30° Displayable colours (millions) 1073.4 Horizontal scan rate 15 ~ 140Khz Vertical scan rate 24 ~ 120Hz Uniformity 75%

0.79m ~ 8.18m (31" ~ 322") diagonal Screen size

Lamp info

Light source type LASER life 30,000 hours

Optical

1.16:1 ~ 1.49:1 Throw ratio Projection distance (m) 1m - 8m Zoom 1.3 Manual Zoom type Focal length (mm) 16.9 ~ 21.61 Native offset 116%

Connectivity

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General

29dB Noise level (min) Noise level (max) 35dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz 2D compatibility

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D) 3D

Full 3D

Security Security bar, Kensington Lock, Password protected interface IP6X

IP rating

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, OSD / display languages

Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2500m

Remote control Card style Speaker count 15W Watts per speaker

In the box AC power cord Remote control 1x CR2025 battery

Basic user manual Optional wireless models

Power

External power supply, 100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) <0.5W Power consumption (min) 119W Power consumption (max) 173W

Weight and dimensions

274 x 216 x 114 Dimensions (W x D x H) mm 4.2 kg Gross weight Net weight 3 kg



