

X416

Compact and powerful



- **Bright XGA projector – 4300 ANSI lumens**
- **Installation flexibility – Vertical lens shift and 1.36x zoom**
- **Ultimate Control - Full support for Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Easy connectivity - HDMI, MHL, VGA, 10W speaker**

Make your presentations count regardless of the ambient light level using the bright X416. Designed for businesses and professional installation environments this compact and powerful projector can be installed or taken on the move.

Easy to connect to with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even present wirelessly using the HDCast Pro (sold separately) or use the USB Power to connect and power HDMI dongles such as the Google Chromecast.



Specifications

Display/image	
Display technology	DLP
Resolution	XGA (1024x768)
Brightness	4,300 lumens
Contrast ratio	20,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	+/-0°
Keystone correction - vertical	+/-40°
Horizontal scan rate	15 ~ 91Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.85m ~ 7.64m (33.62" ~ 300.7") (diagonal)
Lamp info	
Light source type	Lamp
Lamp watts	260
Lamp life (hours)	3000 (Bright), 6000 (Dynamic), 5000 (Eco), 7000 (Eco+)
Optical	
Throw ratio	1.39:1 - 1.9:1
Projection distance (m)	1.3m - 8.5m
Zoom	1.36
Zoom type	Manual
Focal length (mm)	15.98 ~ 21.42
Lens shift	Vertical +17%
Native offset	98%
Connectivity	
Connections	<p>Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 2 x Audio 3.5mm</p> <p>Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A</p> <p>Control 1 x RS232, 1 x RJ45, 1 x mini USB mouse/service</p>
General	
Noise level (typical)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	21 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Romanian, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	249W
Power consumption (max)	309W
Weight and dimensions	
Net weight	2.99kg
Dimensions (W x D x H) mm	315 x 224 x 114

