

# ML750e

Ultra-compact LED projector



- **HD Ready and LED technology - Great for movies, gaming and PC-free presentations**
- **Great connectivity - HDMI, MHL, microSD and built in speaker**
- **Built in media play and optional wireless presentations**
- **Compact & Lightweight <0.4kg**



The ML750e ultra-compact portable LED projector is easily transportable between your home and office. This tiny projector weighs less than 0.4kg and comes with a convenient carry bag. Watch HD movies, play video games or even present that winning presentation, the ML750e has everything you need to impress your audience.

## Specifications

EAN: 5055387600256, Colour: Black

### Display/image

Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	700/450
Contrast ratio	20.000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	0.43m ~ 2.54m (17" ~ 100") diagonal

### Lamp info

Light source type	LED
LED life	20.000 hours

### Optical

Throw ratio	1.5:1
Projection distance (m)	0.55m - 3.23m
Zoom type	Fixed
Focal length (mm)	14.95
Native offset	100%

### Connectivity

Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card, 1 x USB-A reader, 1 x Universal I/O - VGA
-------------	---

### General

Noise level (min)	30dB
Noise level (max)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C ~ 35°C, Max. Humidity 85%, Max. Altitude 2500m
Remote control	Card style
Speaker count	1
Watts per speaker	1W
In the box	Carry bag Universal I/O cable AC power cord Remote control Battery Basic user manual

Input lag	16.00ms
Optional wireless models	WUSB

### Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	45W
Power consumption (max)	65W

### Weight and dimensions

Dimensions (W x D x H) mm	105 x 106 x 39
Gross weight	1.31 kg
Net weight	0.38 kg

